

ProLite T115 15" Touch Screen Monitor

The Digital Yacht ProLite T115 is based on the latest 5 Wire Resistive technology. The combination of price, performance, size, 12v DC supply and touch screen, make this an ideal monitor for marine applications. The display includes both analogue (VGA) and Digital (DVI) inputs and touchscreen connectivity via USB or RS232 interfaces. The removable stand is attached using a standard VESA 75mm mount, so connecting other brackets or panel mounting is very easy. The touch screen has four point calibration and duplicates all of the normal Windows Mouse controls, making operation easy in even the roughest conditions.



Panel	TN
Diagonal	15"
Touchtechnology	resistive
Light transmittance	80%
Display area h x w	228.1 x 304.1 mm; 9" x 12"
Response time	16 ms
Contrast	500 : 1 with touch panel
Brightness	200 cd/m
Viewing zone	horizontal/vertical: 120°/100°; right/left: 60°/60°; up/down: 40°/60°
Display colour	16.2 million
Pixel pitch h x v	0.297 x 0.297 mm
Native resolution	1024 x 768 (0.8 megapixel)
Horizontal sync	31 - 60 KHz
Vertical sync	60 - 75 Hz
Bandwidth	80 MHz
Analog input connector	D-Sub
Digital input connector	DVI-D
Interface	RS-232C, USB
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	AC adapter, power cable, D-Sub signal cable, DVI-D signal cable, RS-232C signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), quick start guide, safety manual
Apple - Mac	OSX
Controls	On-Screen-Display in 7 languages (EN, DE, ES, FR, IT, JP, Chinese) and 5 Front controls (Menu, Brightness, Volume, Input, Power)
User controls	contrast, brightness, volume, auto set-up, V-position, H-position, OSD language, clock, phase, colour temperature, reset
Driver	Windows (Vista, XP, 9X, 2000, CE, NT4), Linux, Mac OSX, DOS
Safety	CE, TÜV-SUD
Power supply	DC12V, 4A
Power Supply Unit	external
Power usage	max. 23 W in normal use; max. 2 W in Power management mode
Power management	VESA DPMS
VESA mounting	75 mm x 75 mm
Tilt angle	90° up; 5° down
Dimensions w x h x d	351 x 280 x 140 mm (Height on Stand = 314.5mm)
Weight	4.3 kg
Aspect ratio	4 : 3

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.